



Feature:

- *VGA、HDMI、CVBS sync output
- *VGA、HDMI output 1920×1080
- *Support AHD and 960H camera
- *Support preview image or image amplification
- *Support mobile phone monitoring(iPhone, Android Windows Mobile, BlackBerry,Symbian)
- *Support P2P

Model	AZ-AHD-1004AD	AZ-AHD-1008AD
System		
Main processor	High performance embedded microprocessor	
OS	Embedded Linux OS	
Video		
Image standard	H.264	
Switch model	4ch AHD 720P or 2ch AHD 720P+2ch 960H	8ch AHD 720P or 4ch AHD 720P+4ch 960H
Recording&Playback	PAL:720P @ 50FPS NTSC: 720P @ 60FPS	PAL:720P @ 50FPS NTSC: 720P @ 60FPS
Language	English,French,German,Italy,Poland、 Portugal、 Russia、 Spanish、 Thai.....	
Motion detection	Each cam can set 192pcs area (16*12) ,Sensitivity level: 1-6	
Area mask	Support	
Recording		
Recording mode	Manual ,motion, timer ,alarm recording	
Recording storage	HDD , Network	
Recording Speed	30 fps NTSC;25fps PAL	
Playback	Local: 4CH ; Remote: 4CH	
Backup mode	Support HDD, USB pen drive Storage and backup	

Video	
Video output	1CH VGA ,1CH HDMI ,1CH BNC
Audio	
Audio input	4 channel
Audio output	1 channel
Alarm	
Alarm input	NO
Alarm output	NO
Others	
Network	1x10/100Mbps,RJ45 interface
Commnication	RS485
USB	2 USB2.0, Support upgrade via usb pen drive
HDD	1HDD sata port ,Max to 3TB
Power	DC +12V /2A
Consumption	<12W (Not included HDD)
Working temprature	0℃ – +55℃
Working humidity	10% – 90%
Size	252*213*42mm (Height 0.8u)
Weight	2KG



Feature:

- *VGA、HDMI、CVBS sync output
- *VGA、HDMI output 1920×1080
- *Support AHD or IP or 960H camera
- *Support preview image or image amplification
- *Support mobile phone monitoring(iPhone, Android Windows Mobile, BlackBerry,Symbian)
- *Support P2P

Model	MAR-1004HD	MAR-1008HD
System		
Main processor	High performance embedded microprocessor	
OS	Embedded Linux OS	
Video		
Image standard	H.264	
Switch model	4ch AHD 720P or 4ch 960H or 2ch 1080P+2ch 720P	8ch AHD 720P or 8ch 960H or 1ch 1080P+8ch 720P
Recording&Playback	PAL:720P @ 50FPS NTSC: 720P @ 60FPS	PAL:720P @ 50FPS NTSC: 720P @ 60FPS
Language	English,French,German,Italy,Poland、Portugal、Russia、Spanish、Thai.....	
Motion detection	Each cam can set 192pcs area (16*12) ,Sensitivity level: 1-6	
Area mask	Support	
Recording		
Recording mode	Manual ,motion, timer ,alarm recording	
Recording storage	HDD , Network	
Recording Speed	30 fps NTSC;25fps PAL	
Playback	Local: 4CH ; Remote: 4CH	
Backup mode	Support HDD, USB pen drive Storage and backup	
Video		
Video output	1CH VGA ,1CH HDMI ,1CH BNC	
Audio		
Audio input	4 channel	
Audio output	1 channel	
Alarm		
Alarm input	NO	
Alarm output	NO	
Others		
Network	1x10/100Mbps,RJ45 interface	

Commnication	RS485
USB	2 USB2.0, Support upgrade via usb pen drive
HDD	1HDD sata port ,Max to 3TB
Power	DC +12V /2A
Comsumption	<12W (Not included HDD)
Working temprature	0℃ – +55℃
Working humidity	10%–90%
Size	248*210*43mm
Weight	2KG