



Spy Security Systems

LIXT90SHD Weatherproof IR Camera with 3-Axis

Model	LIXT90SHD	
Image Sensor	1/3" SONY ICX639BK CCD	
Horizontal Resolution	700TV Lines Low Illumination, DWDR, OSD	
Pixels	PAL:795 (H)× 596(V)	
Usable Illumination	0.001Lux/F2.0	
TV System	PAL/NTSC	
IR LED	ϕ 8 X36PCS	
IR Series Distance	50M	
Lens	4-9mm Manual Zoom lens	
Sync System	Internal	
IR Status	Under 10 Lux By CDS	
Usable Illumination	0 Lux/F2.0 (LED ON)	
IR Power On	CDS Auto Control	
S/N Ratio	≥65dB (AGC OFF)	≥54dB (AGC OFF)
Gamma Correction	0.45	
Video Out	Composite Signal (1.0Vp-p, 75Ω)	
Scanning System	PAL: 625 Lines, 50 Field/Sec; NTSC: 525 Lines, 60 Field/Sec	
Electronic Shutter Time	Auto: PAL 1/50-1/100,000Sec; NTSC 1/60-1/100, 000Sec	
Operation Temperature	-10°C ~ +50°C RH95% Max	
Storage Temperature	-20°C ~ +60°C RH95% Max	
White Balance	Auto	
Power Source	DC12V 700mA	
Dimension	259(W)x159(H)x104(D)mm	

